

VERSO

Version

White - 55 cm - 800 m³/h

Collection

Design

EAN code

8034122358758



*The photograph is purely for information
It may not correspond to the selected version.*

FEATURES

Tempered glass
Touch control + 24 h function
Metallic grease filter, removable and washable
Optional combined regenerable Carbon.Zeo filter
Charcoal filter included
Possible to duct wall mounted from rear
Optional Chimney
Dynamic LED Light (2700K - 5600K)

OPTIONAL ACCESSORIES

KACL.770#41F
 Remote under-roof 1100 m³/h
 Brushless
KACL.786#41F
 Outdoor extractor fan 1000 m³/h
KACL.796#4AF
 Outdoor extractor fan 1500 m³/h
KACL.797#4AF
 Remote under-roof motor 1300 m³/h
KACL.798#41F
 Remote under-roof motor 950 m³/h
KACL.941
 External filter unit for sloped hoods
KCQAN.00#B
 Optional Chimney (White)

TECHNICAL FEATURES

Installation type
 Wall
Dimensions
 55 cm
Finishing
 White tempered glass
Motor
 800 m³/h
Type of control
 Touch control
Speed settings
 4
Lighting
 Led 2x1,2 W - 3200 K
Charcoal filter
 Round charcoal filter Ø170 mm - Type 6 (optional)
Minimum distance
 Gas hob: 52 cm
 Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES



Gross weight
 19.7 kg
Net weight
 16.2 kg
Volumes
 0.19 m³
Packaging size
 Length
 710 mm
 Height
 450 mm
 Depth
 595 mm

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption
 280 W
Voltage
 220-240V
Frequency
 50-60Hz
Plug type
 Shuko

MOTOR TECHNICAL SHEET

Maximum capacity
 750 m³/h
 I.E.C. 61591
Maximum noise level
 66 dB(A)re1pW
 I.E.C.60704-2-13
Maximum pressure (Pa)
 510 Pa
Max. motor power
 224 W
ENERGY CLASS
 A



VERSO

Version

White - 55 cm - 800 m³/h

Collection

Design


EAN code

8034122358758

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	46	53	58	66
Capacity (m ³ /h) I.E.C.61591	295	390	500	750
Maximum pressure (Pa)	390	440	490	510
Motor Power (W)	130	150	178	224
Air outlet	150	150	150	150

CAPACITY / PRESSURE




VERSO

Version
White - 55 cm - 800 m3/h

Collection
Design

EAN code
8034122358758

ENERGY LABEL



PF		
S	Falmec Spa	
M	White - 55 cm - 800 m3/h	
AEC	53,1	kWh/a
EEC	A	
FDE	31,6	
FDEC	A	
LE	21,6	
LEC	B	
GFE	82,0	
GFEC	C	
Qmin	295,0	m³/h
Qmax	500,0	m³/h
Qboost	750,0	m³/h
SPEmin	46	dBa
SPEmax	58	dBa
SPEboost	66	dBa
PO	-	W
PS	0,48	W
PI		
F	0.9	
EEL	52,7	
Qbep	440,0	m³/h
Pbep	388	Pa
Qboost	750,0	m³/h
Wbep	150,0	W
WL	5,30	W
Emiddle	114	lex
Lwa-SPEmax	58	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). PI_Additional information according to 66/2014 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.